



## AG stop spray nozzle

### Application:

AG stop spray nozzle for rinsing at normal water pressure.

### Construction:

- The valve is opened by bending the rubber spout and closing again when the valve is released
- Stepless adjustable water volume

### Quality:

- Stainless steel valve housing partly embedded in rubber
- The valve parts are made of stainless steel
- Gaskets in nitrile rubber
- Does not withstand steam

### Operating conditions:

- The temperature ranges up to max. +80°C
- Pressure: Max. 5 bar
- Water volume: 40 litres per minute

### Address

Alfotech ApS  
Alstrup Allé 10  
8361 Hasselager  
Danmark

### Contact us

Phone: +45 7020 0422  
Inquiry: [foresporgsel@alfotech.dk](mailto:foresporgsel@alfotech.dk)  
Order: [orders@alfotech.dk](mailto:orders@alfotech.dk)  
VAT: 26869617

Item number	Max. temperature C	Kapacitet - liter/min	Working pressure bar	Base unit
0583000000	80°C	40,0	5,0	PCS

## Address

Alfotech ApS  
Alstrup Allé 10  
8361 Hasselager  
Danmark

## Contact us

Phone: +45 7020 0422  
Inquiry: [foresporgsel@alfotech.dk](mailto:foresporgsel@alfotech.dk)  
Order: [orders@alfotech.dk](mailto:orders@alfotech.dk)  
VAT: 26869617